

## Potlatch Precision Core™ Plywood Glue- Line Limited Warranty

Potlatch Precision Core™ plywood is warranted from the date of the original installation for a period of 25 years, against delamination from exposure to normal weather conditions, excluding flood or prolonged water immersion, provided (a) the material has not suffered damage from storage prior to installation, (b) installation and use are in accordance with generally accepted practices, (c) structural and moisture conditions do not exceed the American Plywood Association recommendations for plywood of this type. This warranty does not cover the effects of surface weathering.

### CONFORMANCE

Should any Precision-Core™ plywood covered by this warranty not conform to the above, Potlatch will, at its' sole option, (1) refund the full purchase price of the plywood, or (2) replace the plywood without charge, provided written notice of the claim is given to Potlatch within 30 days after discovery of the defect comprising the nonconformity, and provided further that reasonable opportunity is given to Potlatch to inspect the material prior to repair or alteration thereof.

POTLATCH MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS SET FORTH ABOVE. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

## PLYWOOD STORAGE INSTRUCTIONS

Prolonged storage of plywood should be in a warehouse and the following rules should be observed where applicable:

1. Plywood should never be stored in direct contact with the ground it should rest on stringers of 2x4s or other supports.
2. Stringers supporting plywood should be level and there should be at least three in the 8-foot length of the panels: one centered and the other two approximately 12 to 16 inches from the ends.
3. Plywood should be covered when stored outside to keep it clean, and to prevent uneven accumulations of moisture which might result in warping or twisting, particularly of the top panels.
4. If plastic sheets or tarps are used, keep them open and away from sides and bottom of units for good air circulation around the panels.

### TIPS ON USING PLYWOOD:

1. Glue and nail your floors for added stiffness and squeak resistance.
2. Space your plywood 1/8" at the ends and 1/8" at the edges.
3. Carbide-tipped saw blades are recommended for cutting.
4. Consult American Plywood Association guidelines for specific installation data.

# Potlatch

**Potlatch Corporation**

W. 201 North River Drive, Suite 380  
Spokane, WA 99201  
Telephone (509) 328-0930  
Fax (509) 327-9409